

Autowave Guncleaner

FOR PROFESSIONAL USE ONLY

설명서 Description

수용성 제품에 사용되는 장비의 세척과 행굼에 적합한 특수 세척제입니다.

제품과 첨가제 Product and additives

제품 : Autowave Guncleaner

첨가제 : Autowave Separator (TDS 6.92)

기본적인 원재료 Basic raw materials

물과 솔벤트

세척 테크닉 Cleaning technique

사용한 장비는 잔여물이 없도록 세척 후 충분히 행굼 내야 합니다. 그 후에 소량의 Activator WB 로 행굼 내시면 더욱 좋습니다.

자동 건세척기 사용 시:

가장 효과적인 자동 건 세척기 사용을 위해서는 기기를 순수한 Autowave Guncleaner 로 채워주시기 바랍니다.

수동 건세척 :

Autowave Guncleaner 는 세척의 목적으로 제조되어진 제품입니다.

만약 수용성 제품이 건조된 상태로 장비에 묻어있다면, Autowave Guncleaner 사용 전에 Sikkens 솔벤트로 닦아 내십시오.

알루미늄 소재의 장비는 Autowave Guncleaner 에 잠기도록 하지 마십시오. 이 제품은 수용성 제품에만 사용되는 스프레이 장비에 적용하도록 특화되어 있는 제품입니다.

보건 및 안전 Health and Safety



사용 전 충분한 환기를 해주십시오. 설치 가능한 적절한 장소에 국부 배출 환기장치가 설치되어야 합니다.

약한 용해력의 탈지제를 사용하는 경우라도 세척 또는 탈지작업 동안 항상 내 용제력이 있는 장갑을 사용하시기 바랍니다. 세척용제가 피부에 흡수되는 위험을 줄일 수 있으며, 손의 염분 및 기름으로 인해 표면이 오염되는 것을 방지할 수 있습니다. 사용한 헝겍은 정기적으로 교체하여 주십시오.

휘발성 유기 화합물 VOC

이 제품의 유기화합물 함유량은 사용하기 위해 혼합된 상태에서 최대 96 g/liter 입니다.

제품의 보관 Product storage

제품의 보존 기간 (shelf-life)은 20°C 에서 개봉되지 않은 상태로 보관 되어진 상태를 기준으로 결정 됩니다. 급격한 온도변화를 피하여 주십시오.

최적의 제품성능을 위해 개봉된 제품은 실사용할 온도에서 보관하여 주십시오.

제품의 보관 및 운반 가능한 온도범위는 2°C~35°C 입니다.

제품 보존 기간 (shelf-life)은 기술 자료 TDS S9.01.02 를 참조 하여 주십시오.

Autowave Guncleaner

FOR PROFESSIONAL USE ONLY

공급사 : (주)노루페인트

www.autorefinishes.co.kr

본사 및 안양공장 : 경기도 안양시 만안구 박달로 351

Tel (031) 467-6114(대) / 1588-7700(제품상담) / 1588-7707 (구입상담)

자동차 보수용도료 기술팀 : Tel (031) 467-6167~9 / Fax (031) 442-6755

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

AkzoNobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. www.sikkensvr.com