

M200

FOR PROFESSIONAL USE ONLY

Description

M200 is a waterborne surface cleaner capable of removing water dissoluble contamination. Use M200 after cleaning with other surface cleaners in the Sikkens assortment.

Pre-Cleaning

Pre-clean the surface with warm water and a pH neutral detergent for optimum cleaning and removal of all water-soluble contamination. Rinse sufficiently with clean water.

Contamination of residual grease, oil, wax and silicones will not be removed.

Cleaning technique

Use the M200 as an afterwipe for optimum surface cleaning to ensure removing all residual substances.

Do not allow the surface cleaner to evaporate there the contamination on the surface will remain. Wipe the surface thoroughly dry before the surface cleaner evaporates.

- Replace cloths being used for degreasing and cleaning regularly by clean ones. Always place used degreasing rags in a sealed container that meets local requirements to avoid the risk of a spontaneous combustion fire.
- Instead of placing used (wet) degreasing rags in a sealed container place them on the floor grating so that the solvents can evaporate, then place the dried cloths in the regular dustbin.
- Where bodyfiller is exposed, avoid contact with M200 or any other type of waterborne surface cleaner.

Health and Safety



Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction still suitable respiratory protection is recommended.

- Wear solvent resistant gloves while cleaning even if working with a low solvent surface cleaners. This will reduce the risk of cleaning solvents being absorbed into the skin and prevent salts and oils on your hands from contaminating the surface to be refinished.
- Replace soiled cloths regularly.

VOC

The VOC content of this product in ready to use form is 196 g/liter.

Product storage

Product shelf-life is determined when products are stored unopened at 20°C.

Avoid too much temperature fluctuation.

Product shelf life data see TDS S9.01.02

FOR PROFESSIONAL USE ONLY

Akzo Nobel Pty Ltd T/A Akzo Nobel Car Refinishes Australia
Address: Unit 3/344 Lorimer Street, Port Melbourne, VICTORIA, 3207
Tel: +61 3 9644 1711

FOR PROFESSIONAL USE WITH SUITABLE HS&E EQUIPMENT

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Head Office

AkzoNobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. www.sikkenscr.com